



Description

Suitable for competition and for daily use, it is a lubricant oil with ester which is formulated to provide total engine protection and immediate acceleration. Moreover, it is especially suitable for low contaminating emission engines; its composition prevents the formation of deposits in the exhaust system, which prolongs its life and engine life. It is suitable for engines with a premix in the fuel and also for those that use an injector lubrication system.

Properties

- Formulated to provide total protection, excellent for ensuring a clean engine and low emissions.
- Its components prevent the formation of deposits, helping to keep the exhaust ports clean.
- It extends the engine's lifespan, preventing any sticking of the piston rings, sweating of spark plugs and the formation of carbonous residues.
- It minimises the emission of fumes, contributing to a reduction in pollution.

Quality levels, approvals and recommendations

- API TC
- APRILIA DFI
- ISO L-EGD
- JASO M345 FD*
- TISI 1040
- *Formal approval

Technical specifications

	UNIT	METHOD	VALUE
Density at 15 °C	g/cm3	ASTM D4052	0.876
Kinematic viscosity at 40 °C	cSt	ASTM D445	56
Kinematic viscosity at 100 °C	cSt	ASTM D445	10
Viscosity index	-	ASTM D2270	140
Flash point, open cup	°C	ASTM D92	130
Pour point	°C	ASTM D97	-33
Sulphated ashes	% in weight	ASTM D874	0.1
TBN	mg KOH/g	ASTM D2896	2